Database

Caller

Caller

Query type

Any

Slow queryes

Any

Database

Any

SWAP PLACEHOLDERS

```
SELECT session FROM sessions WHERE sid = :sid LIMIT 0, 1
```

Time: 0.53 ms **Caller**: S\C\H\S\S\H\WriteCheckSessionHandler::read **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_config WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.53 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT config.name AS name FROM config config WHERE (collection =
:db_condition_placeholder_0) AND (nameLIKE :db_condition_placeholder_1
ESCAPE '\\') ORDER BY collection ASC, name ASC
```

Time: 0.67 ms **Caller**: D\C\C\CachedStorage::findByPrefix **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_discovery WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.45 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT * FROM users_field_data u WHERE u.uid = :uid AND u.default_langcode
= 1
```

Time: 1.24 ms **Caller**: D\u\A\P\Cookie::authenticate **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT roles_target_id FROM user__roles WHERE entity_id = :uid
```

Time: 1.3 ms **Caller**: D\u\A\P\Cookie::authenticate **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.85 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.88 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, route, fit FROM router WHERE pattern_outline IN (
:patterns__0, :patterns__1, :patterns__2 ) ANDnumber_parts >= :count_parts
```

Time: 1.15 ms **Caller**: D\C\R\RouteProvider::getRouteCollectionForRequest **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.91 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::getCurrentChecksum

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_data (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
```

```
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 2.63 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.73 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_bootstrap WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.6 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT revision.vid AS vid, revision.langcode AS langcode,
revision.revision_timestamp AS revision_timestamp,
revision.revision_uid AS revision_uid,
revision.revision_log AS revision_log, base.nid AS nid, base.type AS type,
base.uuid AS uuid, CASE base.vid WHEN revision.vid THEN 1 ELSE 0 END ASisDe
faultRevision FROM node base INNERJOIN node_revision
revision ONrevision.vid =
base.vid WHERE (base.nid IN (:db_condition_placeholder_0))
```

Time: 0.78 ms **Caller**: D\C\E\S\SqlContentEntityStorage::doLoadMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT revision.* FROMnode_field_revision
revision WHERE(revision.nid IN(:db_condition_placeholder_0)) AND (revision.
vid IN(:db_condition_placeholder_1)) ORDER BY revision.nid ASC
```

Time: 0.87 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM node__body
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.78 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM node__comment
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.69 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM node__field_country
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.64 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMnode__field_date_of_update
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.63 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM node__field_entryid
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
```

```
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.62 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT ces.* FROMcomment_entity_statistics
ces WHERE(ces.entity_id IN(:db_condition_placeholder_0)) AND (ces.entity_ty
pe = :db_condition_placeholder_1)
```

Time: 0.77 ms **Caller**: null::comment_entity_storage_load **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::getCurrentChecksum

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_entity (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.92 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT config.name AS name FROM config config WHERE (collection =
:db_condition_placeholder_0) AND (nameLIKE :db_condition_placeholder_1
ESCAPE '\\') ORDER BY collection ASC, name ASC
```

Time: 0.63 ms **Caller**: D\C\C\CachedStorage::findByPrefix **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.id AS id,
base_table.id AS base_table_id FROM group_content
base_table INNER JOIN group_content_field_data
group_content_field_data ON group_content_field_data.id =
base_table.id WHERE(group_content_field_data.type IN(:db_condition_placehol
der_0)) AND (group_content_field_data.entity_id IN(:db_condition_placeholde
r_1)) AND (group_content_field_data.default_langcode IN (:db_condition_plac
eholder_2))
```

Time: 0.96 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.38 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.52 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.33 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT 1 AS expression FROM node_access node_access WHERE (grant_view >=
:db_condition_placeholder_0) AND(( (nid =
:db_condition_placeholder_1) AND (langcode = :db_condition_placeholder_2)
)OR (nid = :db_condition_placeholder_3) )AND((
(gid IN(:db_condition_placeholder_4)) AND (realm =
:db_condition_placeholder_5) )OR(
(gid IN (:db_condition_placeholder_6)) AND(realm =
:db_condition_placeholder_7) ))LIMIT 1 OFFSET 0
```

Time: 1.05 ms **Caller**: D\n\NodeAccessControlHandler::checkAccess **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, value FROM key_value WHEREname IN ( :keys__0 ) AND collection
= :collection
```

Time: 1.05 ms **Caller**: D\C\S\State::getMultiple **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_dynamic_page_cache WHERE cid IN ( :cids__0
) ORDER BY cid
```

Time: 0.47 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 1.1 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 1.41 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT config.name AS name FROM config config WHERE (collection =
:db_condition_placeholder_0) AND (nameLIKE :db_condition_placeholder_1
ESCAPE '\\') ORDER BY collection ASC, name ASC
```

Time: 0.62 ms **Caller**: D\C\C\CachedStorage::findByPrefix **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_default WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.73 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.58 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.68 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.53 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.51 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.56 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.45 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_default WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.54 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.3 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_default WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.37 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_config WHERE cid IN ( :cids__0, :cids__1
) ORDER BY cid
```

Time: 0.53 ms **Caller**: D\C\C\ChainedFastBackend::getMultiple **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_config WHERE cid IN ( :cids__0, :cids__1
) ORDER BY cid
```

Time: 0.55 ms **Caller**: D\C\C\ChainedFastBackend::getMultiple **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_config WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.48 ms **Caller**: D\C\C\ChainedFastBackend::getMultiple **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 1.19 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base.uid AS uid, base.uuid ASuuid,
base.langcode AS langcode FROMusers base WHERE (base.uid IN(:db_condition_p
laceholder_0))
```

Time: 0.61 ms **Caller**: D\C\E\S\SqlContentEntityStorage::doLoadMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT data.* FROM users_field_data dataWHERE (data.uid IN(:db_condition_pl
aceholder_0)) ORDER BY data.uid ASC
```

Time: 0.56 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM user__roles
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.6 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_about_me
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.68 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_facebook_link
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.7 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_first_name
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
```

```
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.63 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_last_name
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.63 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_linkedin_link
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.61 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_location_country
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.54 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_my_interests
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.66 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_passports_held_for
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 1.16 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_twitter
t WHERE(entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 1.01 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_work_job_title
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.78 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROMuser__field_profile_work_organisation
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.67 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT t.* FROM user__user_picture
tWHERE (entity_id IN(:db_condition_placeholder_0)) AND (deleted =
:db_condition_placeholder_1) AND (langcode IN(:db_condition_placeholder_2,
:db_condition_placeholder_3, :db_condition_placeholder_4,
:db_condition_placeholder_5,
:db_condition_placeholder_6)) ORDER BY delta ASC
```

Time: 0.53 ms **Caller**: D\C\E\S\SqlContentEntityStorage::mapFromStorageRecords

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.48 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::getCurrentChecksum

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_entity (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.6 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_default WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.63 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, value FROM key_value WHEREname IN ( :keys__0 ) AND collection
= :collection
```

Time: 0.51 ms **Caller**: D\C\S\State::getMultiple **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.71 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.57 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1,
:tags__2, :tags__3, :tags__4, :tags__5, :tags__6 )
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::getCurrentChecksum

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.44 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
```

```
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.6 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT name, value FROM key_value WHEREname IN ( :keys__0 ) AND collection
= :collection
```

Time: 0.51 ms **Caller**: D\C\C\E\Q\Query::loadRecords **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 3.79 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 1.38 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 1.09 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.73 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.61 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.35 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.61 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.59 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.58 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.42 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.revision_id AS revision_id,
base_table.id AS id FROMblock_content base_table INNER JOIN block_content
block_content ONblock_content.id =
base_table.id INNERJOIN block_content_field_data
block_content_field_data ON block_content_field_data.id =
base_table.id WHERE (block_content.uuid IN (:db_condition_placeholder_0)) A
ND (block_content_field_data.default_langcode IN (:db_condition_placeholder
_1))
```

Time: 0.58 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.4 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.59 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.41 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.43 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, route, fit FROM router WHERE pattern_outline IN (
:patterns__0, :patterns__1, :patterns__2 ) ANDnumber_parts >= :count_parts
```

Time: 0.52 ms **Caller**: D\C\R\RouteProvider::getRouteCollectionForRequest **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_data (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.76 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_default WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.55 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT config.name AS name FROM config config WHERE (collection =
:db_condition_placeholder_0) AND (nameLIKE :db_condition_placeholder_1
ESCAPE '\\') ORDER BY collection ASC, name ASC
```

Time: 0.74 ms **Caller**: D\C\C\CachedStorage::findByPrefix **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_menu WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT menu_tree.menu_name AS menu_name,
menu_tree.route_name AS route_name,
menu_tree.route_parameters AS route_parameters, menu_tree.url AS url,
menu_tree.title AS title, menu_tree.description AS description,
menu_tree.parent AS parent, menu_tree.weight AS weight,
menu_tree.options AS options, menu_tree.expanded AS expanded,
menu_tree.enabled AS enabled, menu_tree.provider AS provider,
menu_tree.metadata AS metadata, menu_tree.class AS class,
menu_tree.form_class AS form_class, menu_tree.id AS id FROM menu_tree
menu_tree WHERE (route_name =
:db_condition_placeholder_0) AND (route_param_key =
:db_condition_placeholder_1) AND (menu_name =
:db_condition_placeholder_2)ORDER BY depth ASC, weight ASC, id ASC
```

Time: 0.63 ms **Caller**: D\C\M\MenuTreeStorage::loadByRoute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT menu_tree.id AS id FROM menu_tree menu_tree WHERE (menu_name =
:db_condition_placeholder_0) AND (expanded =
:db_condition_placeholder_1) AND (has_children =
:db_condition_placeholder_2) AND (enabled =
:db_condition_placeholder_3) AND (parent IN (:db_condition_placeholder_4))
AND (id NOT IN(:db_condition_placeholder_5))
```

Time: 0.52 ms **Caller**: D\C\M\MenuTreeStorage::getExpanded **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT menu_tree.id AS id FROM menu_tree menu_tree WHERE (menu_name =
:db_condition_placeholder_0) AND (expanded =
:db_condition_placeholder_1) AND (has_children =
:db_condition_placeholder_2) AND (enabled =
:db_condition_placeholder_3) AND (parent IN (:db_condition_placeholder_4,
:db_condition_placeholder_5, :db_condition_placeholder_6,
:db_condition_placeholder_7, :db_condition_placeholder_8,
:db_condition_placeholder_9, :db_condition_placeholder_10,
:db_condition_placeholder_11)) AND (idNOT IN (:db_condition_placeholder_12,
:db_condition_placeholder_13, :db_condition_placeholder_14,
:db_condition_placeholder_15, :db_condition_placeholder_16,
:db_condition_placeholder_17, :db_condition_placeholder_18,
:db_condition_placeholder_19))
```

Time: 0.59 ms **Caller**: D\C\M\MenuTreeStorage::getExpanded **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_menu WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.91 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0, :cids__1,
:cids__2, :cids__3, :cids__4, :cids__5, :cids__6, :cids__7, :cids__8,
:cids__9, :cids__10, :cids__11, :cids__12, :cids__13, :cids__14, :cids__15,
:cids__16, :cids__17, :cids__18, :cids__19, :cids__20, :cids__21,
:cids__22, :cids__23, :cids__24, :cids__25, :cids__26, :cids__27,
:cids__28, :cids__29, :cids__30, :cids__31, :cids__32, :cids__33,
:cids__34, :cids__35, :cids__36, :cids__37, :cids__38, :cids__39,
:cids__40, :cids__41, :cids__42, :cids__43, :cids__44, :cids__45,
:cids__46, :cids__47, :cids__48, :cids__49, :cids__50, :cids__51,
:cids__52, :cids__53, :cids__54, :cids__55, :cids__56, :cids__57,
:cids__58, :cids__59, :cids__60, :cids__61, :cids__62, :cids__63,
:cids__64, :cids__65, :cids__66, :cids__67, :cids__68, :cids__69,
:cids__70, :cids__71, :cids__72, :cids__73 ) ORDER BY cid
```

Time: 1.7 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.37 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.53 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.33 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.47 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.64 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.48 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.48 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.44 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.33 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.3 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.87 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, value FROM key_value WHEREname IN ( :keys__0 ) AND collection
= :collection
```

Time: 0.45 ms **Caller**: D\C\C\E\Q\Query::loadRecords **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.56 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1,
:tags__2, :tags__3, :tags__4 )
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.37 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1,
:tags__2 )
```

Time: 0.35 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT menu_tree.menu_name AS menu_name,
menu_tree.route_name AS route_name,
menu_tree.route_parameters AS route_parameters, menu_tree.url AS url,
menu_tree.title AS title, menu_tree.description AS description,
menu_tree.parent AS parent, menu_tree.weight AS weight,
menu_tree.options AS options, menu_tree.expanded AS expanded,
menu_tree.enabled AS enabled, menu_tree.provider AS provider,
menu_tree.metadata AS metadata, menu_tree.class AS class,
menu_tree.form_class AS form_class, menu_tree.id AS id FROM menu_tree
menu_tree WHERE (route_name =
:db_condition_placeholder_0) AND (route_param_key =
:db_condition_placeholder_1) AND (menu_name =
:db_condition_placeholder_2)ORDER BY depth ASC, weight ASC, id ASC
```

Time: 0.58 ms **Caller**: D\C\M\MenuTreeStorage::loadByRoute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.35 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.35 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.58 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.38 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.43 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.36 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.36 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.3 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.4 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.65 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.39 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, route, fit FROM router WHERE pattern_outline IN (
:patterns__0, :patterns__1, :patterns__2 ) ANDnumber_parts >= :count_parts
```

Time: 0.61 ms **Caller**: D\C\R\RouteProvider::getRouteCollectionForRequest **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_data (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.79 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.61 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.source AS source FROMurl_alias
url_alias WHERE (alias LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.51 ms **Caller**: D\C\P\AliasManager::getPathByAlias **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.37 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, route, fit FROM router WHERE pattern_outline IN (
:patterns__0, :patterns__1, :patterns__2 ) ANDnumber_parts >= :count_parts
```

Time: 0.42 ms **Caller**: D\C\R\RouteProvider::getRouteCollectionForRequest **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_data (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
```

```
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.67 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.59 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT name, route, fit FROM router WHERE pattern_outline IN ( :patterns__0
) ANDnumber_parts >= :count_parts
```

Time: 0.45 ms **Caller**: D\C\R\RouteProvider::getRouteCollectionForRequest **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_data (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.76 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.95 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.53 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.33 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.55 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::getCurrentChecksum

Database: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 1.69 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.44 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1,
:tags__2, :tags__3 )
```

Time: 0.4 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT COUNT(*) AS expression FROMnode_access node_access WHERE (nid =
:db_condition_placeholder_0) AND (grant_view >=
:db_condition_placeholder_1) AND((
(gid IN (:db_condition_placeholder_2)) AND (realm =
:db_condition_placeholder_3) )OR(
(gid IN(:db_condition_placeholder_4)) AND (realm =
:db_condition_placeholder_5) ))
```

Time: 0.83 ms **Caller**: D\n\NodeAccessControlHandler::checkAllGrants **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.61 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.id AS id,
base_table.id AS base_table_id FROM group_content
base_table INNER JOIN group_content_field_data
group_content_field_data ON group_content_field_data.id =
base_table.id WHERE(group_content_field_data.type IN(:db_condition_placehol
der_0)) AND (group_content_field_data.entity_id IN(:db_condition_placeholde
r_1)) AND (group_content_field_data.default_langcode IN (:db_condition_plac
eholder_2))
```

Time: 2.62 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT 1 AS expression FROM node_access node_access WHERE (grant_update >=
:db_condition_placeholder_0) AND(( (nid =
:db_condition_placeholder_1) AND (langcode = :db_condition_placeholder_2)
)OR (nid = :db_condition_placeholder_3) )AND((
(gid IN(:db_condition_placeholder_4)) AND (realm =
:db_condition_placeholder_5) )OR(
(gid IN (:db_condition_placeholder_6)) AND(realm =
:db_condition_placeholder_7) ))LIMIT 1 OFFSET 0
```

Time: 1.05 ms **Caller**: D\n\NodeAccessControlHandler::checkAccess **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.id AS id,
base_table.id AS base_table_id FROM group_content
base_table INNER JOIN group_content_field_data
group_content_field_data ON group_content_field_data.id =
base_table.id WHERE(group_content_field_data.type IN(:db_condition_placehol
der_0)) AND (group_content_field_data.entity_id IN(:db_condition_placeholde
r_1)) AND (group_content_field_data.default_langcode IN (:db_condition_plac
eholder_2))
```

Time: 1.93 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT 1 AS expression FROM node_access node_access WHERE (grant_delete >=
:db_condition_placeholder_0) AND(( (nid =
:db_condition_placeholder_1) AND (langcode = :db_condition_placeholder_2)
)OR (nid = :db_condition_placeholder_3) )AND((
(gid IN(:db_condition_placeholder_4)) AND (realm =
:db_condition_placeholder_5) )OR(
(gid IN (:db_condition_placeholder_6)) AND(realm =
:db_condition_placeholder_7) ))LIMIT 1 OFFSET 0
```

Time: 1.08 ms **Caller**: D\n\NodeAccessControlHandler::checkAccess **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.7 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 6.33 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 1.93 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.83 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.5 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 2.98 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.59 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.52 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.51 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.37 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.47 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.3 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.29 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.id AS id,
base_table.id AS base_table_id FROM group_content
base_table INNER JOIN group_content_field_data
group_content_field_data ON group_content_field_data.id =
base_table.id WHERE(group_content_field_data.type IN(:db_condition_placehol
der_0)) AND (group_content_field_data.entity_id IN(:db_condition_placeholde
r_1)) AND (group_content_field_data.default_langcode IN (:db_condition_plac
eholder_2))
```

Time: 0.66 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT base_table.id AS id,
base_table.id AS base_table_id FROM group_content
base_table INNER JOIN group_content_field_data
group_content_field_data ON group_content_field_data.id =
base_table.id WHERE(group_content_field_data.gid IN(:db_condition_placehold
er_0)) AND (group_content_field_data.type IN(:db_condition_placeholder_1))
AND (group_content_field_data.default_langcode IN (:db_condition_placeholde
r_2))
```

Time: 0.83 ms **Caller**: D\C\E\Q\S\Query::execute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0, :cids__1,
:cids__2, :cids__3, :cids__4, :cids__5, :cids__6, :cids__7, :cids__8,
:cids__9, :cids__10, :cids__11, :cids__12, :cids__13, :cids__14, :cids__15,
:cids__16, :cids__17, :cids__18, :cids__19, :cids__20, :cids__21
) ORDER BY cid
```

Time: 0.66 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.48 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.49 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.46 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.45 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.44 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.35 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.39 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.36 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.34 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.33 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.31 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.33 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.39 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.37 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.34 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.34 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.33 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.36 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.34 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.35 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.35 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_entity WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.38 ms **Caller**: D\w\C\CacheBackendWrapper::getMultiple **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.68 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.6 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.62 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.55 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.54 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.55 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.54 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.83 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.97 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 1.81 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 1.65 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.71 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.53 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
```

```
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.54 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.52 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 1.43 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.72 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.57 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.51 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS


```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```


Time: 0.55 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.53 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT url_alias.alias AS alias FROMurl_alias
url_alias WHERE (source LIKE :db_condition_placeholder_0
ESCAPE '\\') AND (langcode IN(:db_condition_placeholder_1,
:db_condition_placeholder_2)) ORDER BY langcode ASC, pid DESC
```

Time: 0.51 ms **Caller**: D\C\P\AliasManager::getAliasByPath **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.77 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
INSERT INTO cache_render (cid, expire, created, tags, checksum, data,
serialized) VALUES (:db_insert_placeholder_0, :db_insert_placeholder_1,
:db_insert_placeholder_2, :db_insert_placeholder_3,
:db_insert_placeholder_4, :db_insert_placeholder_5,
:db_insert_placeholder_6) ON DUPLICATEKEY UPDATE cid
= VALUES(cid), expire = VALUES(expire), created = VALUES(created), tags
```

```
= VALUES(tags), checksum = VALUES(checksum), data = VALUES(data),
serialized = VALUES(serialized)
```

Time: 2 ms **Caller**: D\C\C\DatabaseBackend::setMultiple **Database**: default **Target**: default

INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.53 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.46 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.51 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.39 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.41 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.35 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.4 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.31 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.47 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.38 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT menu_tree.menu_name AS menu_name,
menu_tree.route_name AS route_name,
menu_tree.route_parameters AS route_parameters, menu_tree.url AS url,
menu_tree.title AS title, menu_tree.description AS description,
menu_tree.parent AS parent, menu_tree.weight AS weight,
menu_tree.options AS options, menu_tree.expanded AS expanded,
menu_tree.enabled AS enabled, menu_tree.provider AS provider,
menu_tree.metadata AS metadata, menu_tree.class AS class,
menu_tree.form_class AS form_class, menu_tree.id AS id FROM menu_tree
menu_tree WHERE (route_name =
:db_condition_placeholder_0) AND (route_param_key =
:db_condition_placeholder_1) AND (menu_name =
:db_condition_placeholder_2)ORDER BY depth ASC, weight ASC, id ASC
```

Time: 0.56 ms **Caller**: D\C\M\MenuTreeStorage::loadByRoute **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_render WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.44 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0, :tags__1
)
```

Time: 0.35 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.56 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.36 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.54 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.75 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_menu WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.48 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT tag, invalidations FROM cachetags WHERE tag IN ( :tags__0 )
```

Time: 0.3 ms **Caller**: D\C\C\DatabaseCacheTagsChecksum::isValid **Database**: default

Target: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( :cids__0 ) ORDER BY cid
```

Time: 0.45 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

EXPLAIN INFO SWAP PLACEHOLDERS

```
SELECT cid, data, created, expire, serialized,
tags, checksum FROM cache_data WHERE cid IN ( 'route_provider.route_load:1d
b58a20a2d8ea6f38594c78e9ea91556129fce992268b7cd88a064794c6c6b2ec2a9273eaa63
3930660be67a26ba049b3989d7a9e58179d8ade2fced0a3613b' ) ORDERBY cid
```

Time: 0.62 ms **Caller**: D\C\C\DatabaseBackend::get **Database**: default **Target**: default

SWAP PLACEHOLDERS