

Module
development
tutorial:

pants.module

DrupalCon Brussels
September 22, 2006


Pants? What? Why?

- ▶ We're gonna learn module development by example
- ▶ We all own pants
- ▶ We all wear pants (sometimes)



Pants module history

- ▶ This is Andy Smith.
- ▶ Andy is wearing pants (but not a shirt)
- ▶ Andy wrote the first pants.module



Feature Requirements

- ▶ Track User Pants status
 - Display current status on profile page
 - Allow users to update their “pants status”
 - Show a block of recent pants updates
- ▶ Allow pants updates via XML-RPC



First Steps

- ▶ Check drupal.org for existing similar modules
 - If so, contact the module maintainer - collaborate!
- ▶ Check groups.drupal.org for similar areas of interest
- ▶ Read:
<http://drupal.org/contributors-guide>

Let's get started!

- ▶ We need some files:
 - pants.info
 - pants.install
 - pants.module
- ▶ We need some code
- ▶ No need for pants

pants.info

```
; $Id$  
name = Pants  
description = Tracks pants status for users.
```



pants.install

- ▶ Implement table creation per-type.
- ▶ Ideally support MySQL & Pgsq
- ▶ Include any updates by implementing pants_update_N

```
<?php
function pants_install() {
    switch ($GLOBALS['db_type']) {
        case 'mysql':
        case 'mysqli':
            // Create the pants status table.
            db_query("CREATE TABLE IF NOT EXISTS {pants} (
                uid INTEGER UNSIGNED NOT NULL,
                status INTEGER NOT NULL DEFAULT 0,
                PRIMARY KEY (uid)
            ) /*!40100 DEFAULT CHARACTER SET utf8 */;");
            // Create pants history table.
            db_query(
                "CREATE TABLE IF NOT EXISTS {pants_history} (
                    uid INTEGER UNSIGNED NOT NULL,
                    status INTEGER NOT NULL,
                    changed INTEGER NOT NULL,
                    changed_by INTEGER UNSIGNED NOT NULL,
                    PRIMARY KEY (uid)
                ) /*!40100 DEFAULT CHARACTER SET utf8 */;");
            break;
        case 'pgsql':
            // TODO
            break;
    }
}
```


pants.module

- ▶ Let's get ready for pants.



helper functions

- ▶ By convention “private” helper functions are prefixed by “_<module>”
- ▶ Modules with lots of helpers can use separate “.inc” files to reduce RAM usage.
- ▶ Higher granularity => Better reuse.

```
<?php
function _pants_change($uid) {
    $status = 1 - _pants_get($uid);
    _pants_set($uid, $status);
}

function _pants_get($uid, $readable = FALSE) {
    $status = db_result(db_query("SELECT status FROM {pa
    ));
    return $status;
}

function _pants_set($uid, $status) {
    db_query('DELETE FROM {pants} WHERE uid = %d', $uid
    );
    db_query('INSERT INTO {pants} (uid, status) VALUES (
    );
    db_query('INSERT INTO {pants_history} (uid, status,
    ());
}

function _pants_status($status) {
    return ($status) ? t('On') : t('Off');
}
```

hook_menu

- ▶ Drupal's menu system is multipurpose. It:
 - registers URL-based callbacks (REST)
 - populates navigation menus
 - serves as highlevel access control

```
<?php
function pants_menu($may_cache) {
  $items = array();
  if ($may_cache) {
    $items[] =
      array('title' => t('Change Pants'),
            'path' => 'pants/change',
            'callback' => 'pants_change',
            'type' => MENU_CALLBACK,
            'access' =>
              user_access('change pants status')
            );
  }
  return $items;
}

/**
 * Implementation of hook_perm
 */
function pants_perm() {
  return array('change pants status');
}
```

hook_user

- ▶ Several options implemented:
- “load”: get pants status
- “insert” / “update”: set pants status
- “view” : show pants status on profile page

```
<?php
function pants_user($op, $edit, &$amp;account, $category
) {
    switch ($op) {
        case 'form':
            $form['pants'] =
                array('#type' => 'radios',
                    '#title' => t('Pants'),
                    '#default_value' => $account->pants,
                    '#options' => array(0 => t('Off'), 1 =>
                ),
                '#description' => t('Your current pants
            ),
            );
            return $form;
        case 'load':
            $account->pants = _pants_get($account->uid);
            break;
        case 'insert':
        case 'update':
            _pants_set($account->uid, $edit['pants']);
            unset ($edit['pants']);
            break;
        case 'view' :
            $items[] = array('title' => t('Pants status'),
                'value' => _pants_status(_pant
->uid)),
                'class' => 'user');
            return array('' => $items);
    }
}
```

User Edit

admin

[view](#)

[edit](#)

Account information

Username: *

admin

Your full name or your preferred username: only letters, numbers and spaces

E-mail address: *

webmaster@walkah.net

A valid e-mail address. All e-mails from the system will be sent to this address. The e-mail address will not be made public and will only be used if you wish to receive a new password or notifications by e-mail.

Password:

Confirm password:

To change the current user password, enter the new password in both fields.

Status:

☐ Blocked

☒ Active

Pants:

☐ Off

☐ On

Your current pants status

User View

admin

[view](#)

[edit](#)

History

Blog

[view recent blog entries](#)

Member for

2 weeks 1 day

Pants status

Off

hook_block

- ▶ Again: multiple “modes” for hook_block
 - “list”: used to show available blocks
 - “view”: called with \$delta to display an individual block

```
<?php
function pants_block($op = 'list', $delta = 0) {
    global $user;

    switch ($op) {
        case 'list':
            $blocks[0]['info'] = t('Your Pants');
            $blocks[1]['info'] = t('Recent Pants');
            return $blocks;
        case 'view':
            switch ($delta) {
                case 0:
                    $output .= "<div>". _pants_status(_pants_get
->uid)) . "</div>\n";
                    $output .= l(t('change'), 'pants/change');
                    $block['subject'] = t('Your Pants are:');
                    $block['content'] = $output;
                    return $block;
                case 1:
                    $block['subject'] = t('Recent Pants');
                    $block['content'] = theme('pants_block');
                    return $block;
            }
        }
    }
}
```


Themeable functions

- ▶ Allow themers to override your markup
- ▶ Good idea anytime you're including raw HTML in your code

```
<?php

function theme_pants_block() {
    $result = db_query_range(
        'SELECT u.uid, u.name, p.status, p.changed
        FROM {users} u INNER JOIN {pants_history} p
        WHERE u.status = 1 ORDER BY p.changed DESC',
    );
    $items = array();
    while ($pants = db_fetch_object($result)) {
        $label = ($pants->status) ?
        t('put pants on') : t('took pants off');
        $items[] = theme('username', $pants)
            . ' ' . $label . '<br />'
            . t('@time ago',
                array('@time' => format_interval(time() -
                    $pants->changed)));
    }
    return theme('item_list', $items);
}
```

Once more with AJAX!

- ▶ Drupal 5.0 features jQuery in core
- ▶ jQuery makes JS/AJAX fun!

```
$(document).ready(
function() {
  // Get Drupal basePath
  var path = Drupal.settings.pants.basePath;

  $("#a#pants").click( function() {
    $.get(path + "pants/change", function(result) {
      $(".pants-status").html(result).fadeIn("slow");
    });
    return false;
  });
});
```

Pants block with AJAX

```
<?php
function pants_block($op = 'list', $delta = 0) {
  global $user;

  switch ($op) {
    case 'list':
      $blocks[0]['info'] = t('Your Pants');
      $blocks[1]['info'] = t('Recent Pants');
      return $blocks;
    case 'view':
      switch ($delta) {
        case 0:
          $output .= '<div class="pants-status">';
          $output .= _pants_status(_pants_get($user->uid));
          $output .= "</div>\n";
          $output .= l(t('change'), 'pants/change', array('id' => 'pants'));
          drupal_add_js(array('pants' => array('basePath' => base_path()), 'setting'));
          drupal_add_js(drupal_get_path('module', 'pants') . '/pants.js');
          $block['subject'] = t('Your Pants are:');
          $block['content'] = $output;
          return $block;
        case 1:
          $block['subject'] = t('Recent Pants');
          $block['content'] = theme('pants_block');
          return $block;
      }
    }
  }
}
```

Pants Blocks

Your Pants are:

Off
[change](#)

Recent Pants

- [admin](#) took pants off
1 min 15 sec ago
- [admin](#) put pants on
1 min 17 sec ago
- [admin](#) took pants off
1 min 19 sec ago
- [admin](#) put pants on
1 min 20 sec ago
- [admin](#) took pants off
1 min 30 sec ago
- [admin](#) put pants on
1 min 31 sec ago
- [admin](#) took pants off
1 min 35 sec ago
- [admin](#) put pants on
1 min 53 sec ago
- [admin](#) took pants off
10 hours 5 min ago
- [admin](#) put pants on
10 hours 5 min ago

hook_xmlrpc

- ▶ Allows you to expose callbacks over XML-RPC
- ▶ Re-use core functionality
- ▶ Change pants status from:
 - Desktop Applications
 - Other Sites

```
<?php
function pants_xmlrpc() {
    return array(
        array(
            'drupal.changePants',
            'pants_xmlrpc_change',
            array('array', 'string', 'string'),
            t('Changes pants status for the given user')),
        array(
            'drupal.getPants',
            'pants_xmlrpc_get',
            array('array', 'string', 'string'),
            t('Changes pants status for the given user')));
}

function pants_xmlrpc_change() {
    global $user;

    $user = user_authenticate($username, $password);
    if (!$user-
>uid || !user_access('change pants status', $user)) {
        return xmlrpc_error(1, t('Wrong username or passwo
    ));
    }

    return _pants_change($user->uid);
}
```

Pants References

- ▶ <http://www.nopantsday.com/>
- ▶ http://term.ie/p/browser/drupal_pants/
- ▶ <http://en.wikipedia.org/wiki/Pants>

Developer References

- ▶ <http://api.drupal.org/>
- ▶ <http://groups.drupal.org/>
- ▶ <irc://irc.freenode.net/#drupal>
- ▶ <http://drupal.org/contributors-guide>
- ▶ <http://drupal.org/update/modules>

Thanks!

- ▶ James Walker
- ▶ Bryght Guy
- ▶ [mailto/xmpp :
james@bryght.com](mailto:james@bryght.com)
- ▶ <http://walkah.net/>



pants: off